ITEM: BALL END

MATERIAL: TYPE 316 STAINLESS STEEL.

FITTING TYPE: NON-ADJUSTABLE CABLE END FITTING

SWAGE TYPE: MACHINE HEX SWAGE AT FACTORY (1/8" & 3/16" SIZES

ALSO AVAILABLE IN CABLECRIMP HAND SWAGE STYLE

FOR ATTACHING IN THE FIELD).

POST TYPE: METAL. WOOD POSSIBLE BUT NOT RECOMMENDED. (POSTS NOT

INCLUDED).

FASTENING TO POST: ATTACH THROUGH END/TERMINATION POST HOLES USING A

SCREW-ON BALL END.

FASTENING AT ANGLES: DRILL SLOTS OR ANGLED POST HOLES AND FITTING WILL PIVOT

ON BALL END.

CABLE TENSIONING: NON-ADJUSTABLE FIXED END.

HARDWARE PAIRINGS: USUALLY PAIRED WITH A BALL END TURNBUCKLE. MUST

BE PAIRED WITH A TENSION ADJUSTMENT FITTING, NOT ANOTHER

FIXED END.

SUPPLIER: FEENEY, INC.

BALL END, STAINLESS STEEL

DØ

THREADS-

INSIDE BALL FACE

						*ATTACHMENT
PART#	SWAGE TYPE	CABLE SIZE	THREAD SIZE	BALL END DIA (DØ)	LENGTH (L)	POST DRILL HOLE Ø
3352	MACHINE	1/8"	1/4-28RH	5/8"	1-1/4"	5/16"
3353	MACHINE	3/16"	1/4-28RH	5/8"	1-3/4"	3/8"
3354	MACHINE	1/4"	5/16-24RH	5/8"	2"	7/16"
3355	CABLECRIMP	1/8"	1/4-28RH	5/8"	1-7/8"	5/16"
3356	CABLECRIMP	3/16"	1/4-28RH	5/8"	2-1/4"	3/8"

^{*} IF DESIRED THE BALL END CAN BE SLIGHTLY RECESSED INTO THE POST BY COUNTERBORING WITH A 9/16" DRILL

CableRail Reference Drawing:

BALL END

 DATE:
 05/15/13

 PAGE:
 1 of 1

 REV:
 A (12/18/17) MRJ

 BY:
 DSY

 CHK:
 BWA



2603 Union St., Oakland, CA 94607 P: 800-888-2418 F: 510-893-9484 www.feeneyinc.com